

File Name: Cu Cathode.spec
Issued By: Gena Burch-Zulch
Issue Date: 05/25/2010
Changes: updated

Revised By: Camille Kruse
Revision Date: 06/09/2010
Approved By: Quality Manager
Approval Date: 06/09/2010



Copper Cathode

Univertical Corporation Part #: A-CCPA-AZ, A-CCPF, A-CCPJ

Product Specifications

<u>Element</u>	<u>Specification</u>
Phosphorus	0.0005% maximum
Zinc	0.0010% maximum
Sulfur	0.0025% maximum
Silver	0.0025% maximum
Iron	0.0015% maximum
Nickel	0.0010% maximum
Lead	0.0008% maximum
Tin	0.0010% maximum
Arsenic	0.0005% maximum
Antimony	0.0005% maximum
Bismuth	0.0002% maximum
Tellurium	0.0002% maximum
Selenium	0.0004% maximum
Oxygen	0.0200% maximum
Copper	balance

Addition requirements:

Flat/solid cathode preferred, please call before shipping corrugated or punched cathode
Specification Standard: ASTM B115 Grade 1
C of A required with all shipments

Univertical Corporation's change control policy applies to this material. Non-compliance may result in the return of the material at the supplier's expense. Printed and distributed copies of this document are uncontrolled.